



CERTIFICATE



SPECIFICATION

System Name	MetaRoof-MK-Kliplok+L Feet With C Rail
Roof Type	Metal roof
Tilt Angle	0°-45°
Wind Load	up to 90m/s
Snow Load	1.6KN/m ²
Applicable Solar Module	Framed / Frameless
Panel Layout	Portrait / Landscape
Design Standard	BS EN1991, ASCE7-10, BS 6399, AS-NZS 1170, GB 50009-2012, MS 1553
Material	AL-6005-T6 & SUS304
Color	Sliver / Black
Warranty	10-year

FEATURE

1. Non-penetrating solution. Non-penetrating roof clamp mounting ensure water-tightness.
2. High suitability. A variety of roof clamps suit for all roofing sheets.
3. Simple and quick installation. Simple and quick installation by fixing the clamp to the metal roofs.
4. Expand installation availability . Expand installation availability while there is no suitable fixing purlin under the roof.

INSTALLATION



COMPONENT

- | | | |
|----|--|-------------------|
| 1 | | Rail 4700mm |
| 2 | | Rail 2300mm |
| 3 | | Rail splice |
| 4 | | End Clamp |
| 5 | | Mid Clamp |
| 6 | | Kliplok |
| 7 | | L Feet Kit |
| 8 | | Grounding Lug Kit |
| 9 | | Grounding Clip |
| 10 | | Cable Clip |

OPTION

- | | | |
|---------------|-------------|---------------|
| | | |
| Kliplok 18 | Kliplok 25 | Kliplok 36 |
| | | |
| Kliplok 36 II | Kliplok 50 | Kliplok 305 |
| | | |
| Kliplok 406 | Kliplok 700 | Kliplok 406 H |