



CERTIFICATE



SPECIFICATION

| | |
|--------------------------------|---|
| System Name | MetaRoof-FR-Adjustable Tilt Flat Roof Mounting System |
| Ground Type | AL |
| Tilt Angle | Fixed 10-15°, 15-30°, 30-60° |
| Wind Load | up to 90m/s |
| Snow Load | Up to 60cm |
| Applicable Solar Module | Framed/Frameless |
| Panel Layout | Portrait/Landscape |
| Design Standard | BS EN, ASCE7-10, BS 6399, AS-NZS 1170, GB 50009-2012, MS 1553 |
| Material | AL-6005-T6, SUS304, 410 |
| Color | Sliver/Black |
| Warranty | 10-year |

FEATURE

1. Flexible adjustments. Allow for project-specific adjustments and optimize solar power output.
2. Compact package. Compact package before shipment for easy transportation and retail.
3. Highly applicable. Fit for different metal roofs or open concrete terrain applications.
4. Highly pre-assembled. Highly pre-assembly to save on-site installation time.

INSTALLATION



COMPONENT

- | | | | | | |
|----------|--|-------------|-----------|--|-------------------|
| 1 | | End Clamp | 6 | | Back Leg |
| 2 | | Mid Clamp | 7 | | Expansion Bolt |
| 3 | | Rail | 8 | | Grounding Clip |
| 4 | | Rail Splice | 9 | | Grounding Lug Kit |
| 5 | | Front Leg | 10 | | Cable Clip |